

Serial No.: 10/707,470
Attorney Docket No.: F-670

Patent

RECEIVED
CENTRAL FAX CENTER
MAR 19 2007

Amendment To The Claims

Please amend the claims as follows:

1. (currently amended) An ~~A~~ cleaning apparatus for cleaning non-contact optical sensors in a paper handling device comprising:

a substrate sheet for feeding through a feed path of the paper handling apparatus device having a first surface and a second surface and having a substrate thickness, wherein the first surface has a front edge, a rear edge, a left edge and a right edge;

a first strip of material having a first strip height and attached to the first surface of the substrate sheet and oriented perpendicular to the feed path, wherein the first strip will vertically compress when drawn through a roller nip and partially vertically decompress when exiting the roller nip in order to engage the optical sensors below the feed path;

a second strip of material having a first strip height and attached to the first surface of the substrate sheet and oriented perpendicular to the feed path, wherein the second strip will vertically compress when drawn through a roller nip and partially vertically decompress when exiting the roller nip in order to engage the optical sensors below the feed path; and, wherein,

the first strip is separated from the second strip in the direction of the feed path by a first distance; and

the first strip height is relatively large compared to the substrate thickness and the first strip height when partially decompressed is sufficiently large to extend below the feed path to engage the optical sensors.

2. (original) The apparatus of claim 1, wherein,
the first surface is an upper surface and the second surface is a lower surface.

3. (original) The apparatus of claim 2, wherein,

Serial No.: 10/707,470
Attorney Docket No.: F-670

Patent

the first strip of material comprises open cell foam.

4. (original) The apparatus of claim 3, wherein,
the first strip of material is closer to the front edge of the substrate sheet than
the second strip of material; and
the second strip of material comprises open cell foam and brush bristles.

5. (original) The apparatus of claim 3, wherein,
the first strip of material comprises lint-free, lead-free, non-abrasive, open cell
foam.

6. (original) The apparatus of claim 1, wherein,
the substrate sheet has approximately the planar dimensions of a number 10
envelope.

7. (original) The apparatus of claim 1, further comprising,
a leading edge handle on the substrate sheet.

8. (previously amended) The apparatus of claim 1, wherein,
the substrate sheet has approximately the planar dimensions of a letter sized
sheet of paper and the first strip height is more than double the substrate thickness.

9. (previously presented) The apparatus of claim 1, wherein,
the first strip height is approximately twelve times the substrate thickness.

10. (currently amended) The apparatus of claim 1, wherein,
the first strip having a width that is relatively narrow compared to a diameter of
a roller in order to allow the first strip to vertically decompress when exiting the roller
nip.

Serial No.: 10/707,470
Attorney Docket No.: F-670

Patent

11. (previously presented) The apparatus of claim 1, wherein, the substrate comprises a semi-rigid vinyl material.
12. (previously presented) The apparatus of claim 1, wherein, the substrate comprises an ABS material.
13. (previously presented) The apparatus of claim 1, wherein, the first strip having a first strip width; and wherein the first distance is approximately five times the first strip width.
14. (previously presented) The apparatus of claim 13, wherein, the first strip width is 0.5 inches.
15. (previously presented) The apparatus of claim 1, wherein, the first strip has the shape of a rectangular prism.
16. (canceled).
17. (previously presented) The apparatus of claim 1, wherein, the first strip height is approximately 0.75 inches, the first strip having a width of 0.5 inches; and wherein the first distance is 2.5 inches.
18. (previously presented) The apparatus of claim 1, wherein, at least one of the first and second strips has the shape of a triangular prism.
19. (previously amended) The apparatus of claim 1, wherein, the first strip includes a top surface and has the shape of a rectangular prism having at least one notch in the top surface.

Serial No.: 10/707,470
Attorney Docket No.: F-670

Patent

20. (previously amended) The apparatus of claim 1, wherein,
the first strip includes a leading edge and has the shape of a rectangular prism
having an angled portion of the leading edge removed.

21. (New) The apparatus of claim 1, wherein,
the first strip having a width that is relatively narrow compared to the first
distance in order to allow the first strip to vertically decompress when exiting the roller
nip.